

# CR 250V

## Fall arrester for vertical work

EN 360

CR 250V is intended for work requiring considerable displacement in relation to the point of attachment. No need to use a safety shock absorber. No need to use AZ 800 cable when working horizontally.

### SPECIAL FEATURES



Protection for maximum user's weight of 140 kg



Protection for 1 person



Device for vertical use

### PARAMETERS

**Material** composite

**Min. static strength** 12 kN

#### ROPE

**Diameter Ø** 4 mm

**Material** galvanized steel

#### MECHANISM

**Material** galvanized steel

#### CARABINERS

**Carabiner model** AZ 002ASI

# CR 250V

## Fall arrester for vertical work

### VARIANTS

ref. no.	case colour	length [m]
CR250V06	bright yellow-green	6
CR250V10	bright yellow-green	10
CR250V12	bright yellow-green	12
CR250V15	bright yellow-green	15
CR250V06	black	6
CR250V10	black	10
CR250V12	black	12
CR250V15	black	15
CR250V06	blue	6
CR250V10	blue	10
CR250V12	blue	12
CR250V15	blue	15
CR250V06	grey	6
CR250V10	grey	10
CR250V12	grey	12
CR250V15	grey	15
CR250V06	red	6
CR250V10	red	10
CR250V	red	12
CR250V15	red	15

# CR 250V

Fall arrester for vertical work

PHOTOS 360 (ROTATING)

---

