CONTOUR

LIGHTWEIGHT AND EFFECTIVE

21 g of strength: sturdy, protective, stylish, comfortable and lightweight.
CONTOUR is one of the top three best-selling models.

PLATINUM

CONTPSI

CONTPSF

CONTESP

CONTPOL

21 g

SUPPLIED WITH

Microfibre pouch
ETUIFS

- **NON-SLIP BRIDGE**
- **NON-SLIP TIPGRIP TEMPLES**
- **ANTI-STATIC**

bollé SAFETY

CONTOUR

LIGHTWEIGHT AND EFFECTIVE

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
CONTOUR	Clear	CONTPSI	2C-1,2 1 KN FT CE	EN166 FT CE	Anti-scratch/anti-fog
	Smoke	CONTPSF	5-2,5 1 KN FT CE	EN166 FT CE	Anti-scratch/anti-fog
	ESP	CONTESP	5-1,4 1 FT CE	EN166 FT CE	Anti-scratch
	Polarized	CONTPOL	5-3,1 1 FT CE	EN166 FT CE	Anti-scratch

LENS MARKING

Optical class symbols:

1. Continuous work

Mechanical strength symbols:

F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s
Maximum protection for glasses.

T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

Others symbols:

K. Resistance to surface damage by fine particles (optional)

N. Resistance to fogging (optional)

CE European standard Manufacturer name

FRAME MARKING

EN 166: guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s
Maximum protection for spectacles.

T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

K. Resistance to surface damage by fine particles (optional)

N. Resistance to fogging (optional)

CE European standard Manufacturer name

Bollé Safety product approval certificates to CE standards will be sent on request.

TECHNOLOGY

ESP

ESP, Extra Sensory Perception.
An innovative coating to reduce dazzle and the harmful affects of blue light.
B-ESP filters 57% of blue light, transmits 64% of visible light, 99.99% of UVA/UVB.

POLARIZED

A technology approved for permanent wear and certified with perfect optical quality, it offers unbeatable comfort by filtering glare and reflections. Ideal for the maritime environment. Filters 99.99% of UVA/UVB.

PLATINUM

This permanent coating on both sides of the lens gives them a high resistance to scratching (1.4 cd / m²), to the most aggressive chemicals and delays the onset of fogging for 2 minutes.
In all circumstances and at all times the PLATINUM lens innovation guarantees your eyes improved protection.

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.

PACKAGING AND EAN13 CODE

	CONTPSI	CONTESP	CONTPSF	CONTPOL
Individual plastic bag	3660740003241	3660740003258	3660740003388	3660740000615
10 safety spectacles per inner box	3660740103248	3660740103255	3660740103385	3660740100612
240 safety spectacles per outer pack	3660740203245	3660740203252	3660740203382	3660740200619

CHARACTERISTICS

LENSES	PC - 2,2 mm - Curve 8
FRAME	PC
TEMPLES	Nylon + TPE
STRAP	Non applicable
FOAM	Non applicable

02/03/2017

Europe Bollé Safety
95 rue Louis Guérin
69100 Villeurbanne - France
Tél. : 00 33 (0) 4 78 85 23 64
Fax : 00 33 (0) 4 78 85 28 56
contact@bolle-safety.com

U.K. Bollé Safety
Unit C83 - Barwell Business Park Leatherhead Road - Chessington
Surrey - KT9 2NY
Tél. : 00 44 (0)208 391 4700
Fax : 00 44 (0)208 391 4733
e-mail : sales@bolle-safety.co.uk

bolle-safety.com