

**Reciprocating Piston Compressor**  
**JUMBO C9K-200/3M**  
*Belt driven - one stage*

Automatic start/stop at min/max pressure -  
 two cylinders full cast iron - 200 Lt. CE  
 approved air receiver - manual reset motor  
 thermal protection - large flywheel for high  
 cooling flow - professional compressor -  
 Made in Italy



### TECHNICAL DATA

Max pressure	Bar/Psi	10/145
Air Displacement	L/min	300
	m <sup>3</sup> /h	18
	CFM	10,59
Air receiver capacity	Lt.	200
Motor nominal power	Hp/kW	3 / 2.2
Pump revolutions	Rpm	1500
Power supply	V/Hz/Ph	230/50/1
Cylinder/Stage	no.	2 / 1
Insulation class		F
IP		54
Service factor		S3 50%
Brand/model		FIMA
Cooling system		AIR
Lubrication	type	FIMA Mineral oil (FPM)
Noise level (SPL)	dB(A)	74
Outlet air joint	BSP	1/2"
Weight	Kg	102
Dimensions	(L x D x H) mm	1460 x 640 x 1140

### Conditions of technical data rate

Inlet air pressure	bar (a)	1
Ambient temperature	°C	20
Humidity percentage	%	50
Working Delta pressure range	bar	2
Max ambient temperature	°C	40
Min ambient temperature	°C	5

Technical data ± 5%