

MG 3000 I-HE

+ PORTABLE PETROL ENGINE DRIVEN SINGLE-PHASE GENERATOR / OUTPUT POWER 3KVA SINGLE-PHASE

Gen Set Features

- + Low oil level cut out device
- + 2 x 230 V - 50 Hz Single-phase Schuko outlets protected by circuit breaker
- + 1 x 12V DC battery charger outlet protected by fuse

Gen Set Options
(available as factory options)

- + Not available

Accessories on Request

- + Not available

Noise Level

+ LWA 95	(70 dB at 7m)	Homologated in accordance with the "Directive 2000/14/CE"
----------	---------------	---

AC Generator - 50 Hz

- + Type synchronous
- + Single-Phase Power (stand by) 3 kVA - 230 V
- + Battery Charger 120 W - 12 V - 10 A - DC
- + Power Factor 0,8

Petrol Engine 3000 rpm

- + Type **Honda GX 160 OHV** - 1 cyl. - 5,5 HP (4 kWm) - 163 cm³
- + Fuel petrol
- + Cooling system air
- + Starting system manual recoil
- + Fuel tank capacity 3,6 l
- + Fuel consumption @ 75% 1,3 l/h

Other Features

- + Insulation Class H
- + Mechanical Protection IP 23
- + Dimensions (L x W x H) 585 x 360 x 410 mm
- + Net Weight 42 kg

+ MG 3000 I-HE

 **GenSet**

