

FINN S3



Standard EN ISO 20345 : 2011



UTURN® lacing system

- quick lacing
- made of durable nylon
- precision and adjustment

Size 35 to 49

Ref. FINNS30NR

Product Highlights



- Low shoe available with men's and women's fit.



- **2,0 mm thick high strength leather** (against abrasion, tearing and puncture). Tongue with gusset to prevent any infiltration of dust / stones.

- **Scuffcap TPU injected:** extreme resistance at the front.

- **Memory Foam Titan insock for immediate and lasting comfort:** antibacterial properties, respects foot hygiene.



- **Protective toe-cap:** composite HDFC.



- **Puncture-resistant midsole:** high tenacity fabric "0" penetration.



TRAILIUM PU2D antistatic sole

- **4 mm studs** suitable for construction and heavy duty industry
- **Drainage channels for liquids and mud** to avoid any risk of aquaplaning
- **Lateral edges and 15mm raised heel:** reinforced grip on ladder rungs
- **Large bearing surface,** optimal stability
- **Arch support and heel cushioning:** MSD prevention

USAGE

- Civil engineering and Forestry works
- Logistics, automotive
- Shipyard, construction
- Petrochemistry, chemistry



lemaitre-securite.com

An exacting attitude to quality is our culture, safety our priority



FINN S3



Standard EN ISO 20345 : 2011

Characteristics of the upper

- **Upper material:** smooth full grain water-repellent leather with anti-abrasion TPU scuffcap
- **Tongue/gusset:** water repellent leather
- **Collar:** water repellent leather
- **Lining:** 3D microporous fabric

Characteristics of the sole

- **Designation :** TRAILIUM PU2D
- **Material:** polyurethane / polyurethane
- **Antistatic sole**
- **SRA Adhesion coefficient:**
forward flat slip: 0,34 (standard $\geq 0,32$)
forward heel slip: 0,31 (standard $\geq 0,28$)
- **SRB Adhesion coefficient:**
forward flat slip: 0,20 (standard $\geq 0,18$)
forward heel slip: 0,17 (standard $\geq 0,13$)

VARIANT



Forseti S3 SRC
FORSS30NR

Practical information

Women fitting 35-39

Weight of one shoe size 38:
566 g

CERTIFICATION N°
0075/007/161/07/
19/2226 EXT 19/09/20

Men fitting 40-49

Weight of one shoe size 42:
646 g

CERTIFICATION N°
0075/007/161/07/
19/2226 EXT 20/09/20

Packaging

size 35 to 49

shoebox 345 x 230 x 122 mm

carton 635 x 485 x 355 mm

10 shoeboxes per carton

Gencods

35	3237154408353	43	3237154408438
36	3237154408360	44	3237154408445
37	3237154408377	45	3237154408452
38	3237154408384	46	3237154408469
39	3237154408391	47	3237154408476
40	3237154408407	48	3237154408483
41	3237154408414	49	3237154408490
42	3237154408421		

Memo for basic and additional requirements of the standard EN ISO 20345: 2011

Safety Footwear

SBP



S1



S1P



S2



S3



200 J toe-cap: protection of the forefoot against impact and crushing.



Anti-perforation insert 1100 N: foot protection against perforation.



Anti-static footwear



Insulation against cold



Shock absorption at the heel



Insulation against heat



Fuel oil-resistant outsole



Outsole resistance to hot contact



Water penetration and water absorption resistant upper



Water resistant



Electrostatic discharge



Ankle protection



Slip-resistance on ceramic floors with detergent



Slip-resistance on steel floors with glycerol



$\text{SRC} = \text{SRA} + \text{SRB}$

Lemaitre Sécurité

17 rue de Bitschhoffen - CS 90024
F - 67350 Val de Moder
Tél. +33 (0)3 88 72 28 80

lemaitre-securite.com



LEMAITRE

Safety since 1974

DON_LS 04 TDS 0089
updated: 21/07/21

Member of
SINAMAP

