

# NJORD S3



Standard EN ISO 20345 : 2011



**Ankle protection by Lemaitre**

Malleolus protection against side impacts

**Sizes 35 to 49**

Ref. NJORS30NR

## Product Highlights



▪ **Heavy duty boot** available with men's and women's fit.



▪ **2,0 mm thick high strength leather** (against abrasion, tearing and puncture). Tongue with gusset to prevent any infiltration of dust / stones.

▪ **Scuffcap TPU injected:** extreme resistance at the front.

▪ **Memory Foam Titan insock for immediate and lasting comfort:** antibacterial properties, respects foot hygiene.



▪ **Protective toe-cap:** composite HDFC.



▪ **Puncture-resistant midsole:** high tenacity fabric "0" penetration.



## TRAILIUM PU2D antistatic sole

▪ **4 mm studs** suitable for construction and heavy duty industry

▪ **Drainage channels for liquids and mud** to avoid any risk of aquaplaning

▪ **Lateral edges and 15mm raised heel:** reinforced grip on ladder rungs

▪ **Large bearing surface,** optimal stability

▪ **Arch support and heel cushioning:** MSD prevention

## USAGE

- Civil engineering and Forestry works
- Logistics, automotive
- Shipyard, construction
- Petrochemistry, chemistry



**lemaitre-securite.com**

An exacting attitude to quality is our culture, safety our priority



# NJORD S3



Standard EN ISO 20345 : 2011

## VARIANT



**BALDER S3 SRC**  
BALDS30NR

## Characteristics of the upper

- **Upper material:** smooth full grain water-repellent leather with anti-abrasion TPU scuffcap
- **Tongue/gusset:** water repellent leather
- **Collar:** water repellent leather
- **Lining:** 3D microporous fabric

## Characteristics of the sole

- **Designation :** TRAILIUM PU2D
- **Material:** polyurethane / polyurethane
- **Antistatic sole**
- **SRA Adhesion coefficient:**  
forward flat slip: 0,34 (standard  $\geq 0,32$ )  
forward heel slip: 0,31 (standard  $\geq 0,28$ )
- **SRB Adhesion coefficient:**  
forward flat slip: 0,20 (standard  $\geq 0,18$ )  
forward heel slip: 0,17 (standard  $\geq 0,13$ )

## Practical information

### Women fitting 35-39

Weight of one shoe size 38:  
662 g

**CERTIFICATION N°**  
0075/007/161/07/19/2226  
EXT 17/09/20

### Men fitting 40-49

Weight of one shoe size 42:  
742 g

**CERTIFICATION N°**  
0075/007/161/07/19/2226  
EXT 18/09/20

## Packaging

### size 35 to 39

**shoebox** 345 x 230 x 122 mm

**carton** 635 x 485 x 355 mm

**10 shoeboxes per carton**

### size 40 to 49

**shoebox** 355 x 340 x 130 mm

**carton** 670 x 355 x 360 mm

**5 shoeboxes per carton**

## Gencods

<b>35</b>	3237154403358	<b>43</b>	3237154403433
<b>36</b>	3237154403365	<b>44</b>	3237154403440
<b>37</b>	3237154403372	<b>45</b>	3237154403457
<b>38</b>	3237154403389	<b>46</b>	3237154403464
<b>39</b>	3237154403396	<b>47</b>	3237154403471
<b>40</b>	3237154403402	<b>48</b>	3237154403488
<b>41</b>	3237154403419	<b>49</b>	3237154403495
<b>42</b>	3237154403426		

## Memo for basic and additional requirements of the standard EN ISO 20345: 2011

### Safety Footwear

SBP



S1



S1P



S2



S3



200 J toe-cap: protection of the forefoot against impact and crushing.



Anti-perforation insert 1100 N: foot protection against perforation.



Anti-static footwear



Insulation against cold



Shock absorption at the heel



Insulation against heat



Fuel oil-resistant outsole



Outsole resistance to hot contact



Water penetration and water absorption resistant upper



Water resistant



Electrostatic discharge



Ankle protection



Slip-resistance on ceramic floors with detergent



Slip-resistance on steel floors with glycerol



**SRC = SRA + SRB**

**Lemaitre Sécurité**

17 rue de Bitschhoffen - CS 90024  
F - 67350 Val de Moder  
Tél. +33 (0)3 88 72 28 80

**lemaitre-securite.com**



**LEMAITRE**

Safety since 1974

**DON\_LS 04 TDS 0092**  
updated: 21/07/21

Member of  
**SINAMAP**

