

# THOR S3



Standard EN ISO 20345 : 2011



**WATER RESISTANT**

## UTURN® lacing system

- quick lacing
- made of durable nylon
- precision and adjustment

## Waterproof breathable membrane lining


- 100% waterproof, breathable and anti-bacterial
- optimal ventilation of the foot
- improved comfort
- full upper fitting


Size 35 to 49

Ref. THORS30NR

## Product Highlights

-  Heavy duty boot available with men's and women's fit.

-  Ankle protection by Lemaitre, malleolus protection against side impacts.

-  2,0 mm thick high strength leather (against abrasion, tearing and puncture). Tongue with gusset to prevent any infiltration of dust / stones.

- **Scuffcap TPU injected:** extreme resistance at the front.

- **Memory Foam Titan insock for immediate and lasting comfort:** antibacterial properties, respects foot hygiene.

-  Protective toe-cap: composite HDFC.

-  Puncture-resistant midsole: high tenacity fabric "0" penetration.



## TRAILIUM PU2D antistatic sole

- **4 mm studs** suitable for construction and heavy duty industry
- **Drainage channels for liquids and mud** to avoid any risk of aquaplaning
- **Lateral edges and 15mm raised heel:** reinforced grip on ladder rungs
- **Large bearing surface,** optimal stability
- **Arch support and heel cushioning:** MSD prevention

## USAGE

- Civil engineering and Forestry works
- Logistics, automotive
- Shipyard, construction
- Petrochemistry, chemistry



[lemaitre-securite.com](http://lemaitre-securite.com)

An exacting attitude to quality is our culture, safety our priority



# THOR S3



Standard EN ISO 20345 : 2011

## Characteristics of the upper

- **Upper material:** smooth full grain water-repellent leather with anti-abrasion TPU scuffcap
- **Tongue/gusset:** water-repellent leather
- **Collar:** water-repellent leather
- **Lining:** imper-breathing membrane

## Characteristics of the sole

- **Designation :** TRAILIUM PU2D
- **Material:** polyurethane / polyurethane
- **Antistatic sole**
- **SRA Adhesion coefficient:**  
forward flat slip: 0,34 (standard ≥ 0,32)  
forward heel slip: 0,31 (standard ≥ 0,28)
- **SRB Adhesion coefficient:**  
forward flat slip: 0,20 (standard ≥ 0,18)  
forward heel slip: 0,17 (standard ≥ 0,13)

## VARIANT



Balder S3 SRC  
BALDS30NR

## Practical information

### Women fitting 35-39

Weight of one shoe size 38:  
683 g

**CERTIFICATION N°**  
0075/007/161/07/19/2226  
EXT 25/03/21

### Men fitting 40-49

Weight of one shoe size 42:  
763 g

**CERTIFICATION N°**  
0075/007/161/07/19/2226  
EXT 26/03/21

## Packaging

### size 35 to 39

**shoebox** 345 x 230 x 122 mm

**carton** 635 x 485 x 355 mm

### size 40 to 49

**shoebox** 355 x 340 x 130 mm

**carton** 670 x 355 x 360 mm

10 shoeboxes per carton

5 shoeboxes per carton

## Gencods

35	3237154404355	43	3237154404430
36	3237154404362	44	3237154404447
37	3237154404379	45	3237154404454
38	3237154404386	46	3237154404461
39	3237154404393	47	3237154404478
40	3237154404409	48	3237154404485
41	3237154404416	49	3237154404492
42	3237154404423		

## Memo for basic and additional requirements of the standard EN ISO 20345: 2011

### Safety Footwear

SBP



S1



S1P



S2



S3



200 J toe-cap: protection of the forefoot against impact and crushing.

Anti-perforation insert 1100 N: foot protection against perforation.

<b>A</b>	Anti-static footwear	<b>Ci</b>	Insulation against cold
<b>E</b>	Shock absorption at the heel	<b>Hi</b>	Insulation against heat
<b>Fo</b>	Fuel oil-resistant outsole	<b>Hro</b>	Outsole resistance to hot contact
<b>Wru</b>	Water penetration and water absorption resistant upper	<b>Wr</b>	Water resistant
	Electrostatic discharge	<b>An</b>	Ankle protection

**SRA** Slip-resistance on ceramic floors with detergent

**SRB** Slip-resistance on steel floors with glycerol

**SRC** = **SRA** + **SRB**

Lemaitre Sécurité

17 rue de Bitschhoffen - CS 90024  
F - 67350 Val de Moder  
Tél. +33 (0)3 88 72 28 80

lemaitre-securite.com



**LEMAITRE**  
Safety since 1974

DON\_LS 04 TDS 0093  
updated: 21/07/21

Member of  
**SINAMAP**

