PRODUCT NUMBER: 1032413

Miller kernmantel edge forked shock absorbing lanyard 2 meters with trilock karabiner and 2 GO65 scaffold hooks.

Kernmantel edge forked shock absorbing lanyard 2 meters with an aluminium trilock karabiner and 2 GO65 aluminium scaffold hooks.

Overview

Reference Number
1032413

Product Type
Fall Protection

Range
Shock Absorbing Lanyards

Line
Cut resistant

Brand
Miller by Honeywell

Industry

- Building and Construction
- Utilities

Product Use
Fall arrest lanyards will allow the worker to fall but prevents him from hitting the next lower level, such as the ground, (if well attached). It includes a shock absorber that dissipates the forces exerted on the body in the case of a fall to stay below 6 KN.
This single lanyard is edge tested for safe working on edges (r>= 0,5 mm).

Features & Benefits

Feature
New design : * the new kernmantel lanyard is manufactured with a light green rope with black stripes, which are highly visible from a distance increasing the safety at work. * The stitches are highly visible which facilitates the safety check before use.

Benefit
* The lanyard is edge tested.It is manufactured with high quality kernmantel ropes and have a special cut resistance for safe working on edges (r>= 0,5 mm). * The kernmantel rope is 2 times more resistant to the abrasion than the other standard ropes.

© Honeywell International Inc.

Technical Description

Length
2 M

Weight
1,800 KG

Breaking Strength
> 22 KN

Operating Temperature
-30°C to +50°C

Rope

Rope Raw Material
Kernmantel Ø 11 mm. Polyester sheath. Polyamide core.

Webbing

Webbing Raw Material
Resistant webbing with protective cover

Connector

Connector Type
Trilock karabiner

Connector Raw Material
aluminium

Connector Opening
20 mm

Connector Breaking Strength
> 24 KN

Connector Standard
EN 362 : 2004

Connector

Connector Type
GO55 Scaffold hook

Connector Raw Material
aluminium

Connector Opening
63 mm

Connector Breaking Strength
> 22 KN

Connector Standard
EN 362 : 2004

Certifications

EC Category PPE
3

Quality Assurance
ISO 9001 / 2000

EC Attestation
EC Attestation

EC Attestation Number
0082-490-160-06-13-0170

Certifications

- EN 355 / VG 11 PFE 11.074

REACH

EU Regulation 1907/2006 (REACH) Compliance
The substance(s) listed below may be contained in this product above the threshold level of 0.1% by

© Honeywell International Inc.

weight of the listed article.	
Product Reference Sold in Europe	**Substance > 0.1%**
Substance Name	**CAS Number**
No Substance Content	

Additional Information

User Manual
NT90004208 IND L

User Information Sheet
User manual

Maintenance

Life Cycle
Life expectancy of our harnesses is 10 years from the date of manufacture.

Care Instructions
Some factors can contribute to reduce the performance or life expectancy of the product:

- Incorrect stocking
- Incorrect use
- Stopping a fall
- Mechanical deformation or cut
- Contact with chemical products (an acid or a base)
- Exposure to extreme heat sources > 60°C
- Exposure to UV rays

Please remember that:
- the product must be checked at least once a year by a qualified person. This inspection must be registered.
- before each use, the product must be visually inspected by the user.

The compulsory annual inspection will be the deciding factor as to whether your PPE should be put back into service or not.

© Honeywell International Inc.

© Honeywell International Inc.