Industry-born. Sports-driven.

Data sheet

MILAN 2.0 POWER

GENERAL

Art. no.:	A-029	E-class number:	40-02-01-06
EAN:	4030281155867	Customs no.:	84251900
Standard:	DIN EN 1496-A:2017 DIN EN 341-1A:2011		

SKYLOTEC
Industry-born. Sports-driven.

Data sheet

MILAN 2.0 POWER

MILAN 2.0 POWER is THE special version of the MILAN 2.0 HUB. With the [RESCUE DEVICE DRIVER (RDD)](https://bit.ly/2JrZl7Q) it offers an option for fast and safe rescue over long distances upwards. In addition, all manual options for rescue and evacuation are available.

- electrically operated rescue device with RDD - enables effortless roping up, - maximum lifting weight of 280 kg in emergency

With special [SEAL PACs](https://bit.ly/3408bTx) an extended lifetime of up to 15 years can be guaranteed, which can even be doubled once within a resealing process to 30 years.

Note: When working at heights, a suitable rescue concept based on a risk assessment is essential. MILAN offers a variety of applications for different rescue scenarios. To master these techniques, the user must be carefully trained by a SKYLOTEC-certified instructor who has been specially trained on the device.

GENERAL

Internat. standard:
ANSI Z359.4:2013, MEETS CSA Z259.2.3-1B:2012

FEATURES

Abseiling speed:	0,90 m/s
Abseiling height:	500,00 m
Max. service life:	20 Years
Max. number of persons:	2
Rated load:	260 KG
Temperature:	from 60 °C to -35 °C
Suspension element:	KM9

Area of application:
Fire brigade / Rescue / Special Forces, Metal Construction, Power Supplies / -Transmission / Telecommunications, Wind Energy / Offshore Industry

DIMENSIONS

Weight:	5,07 kg

SKYLOTEC
Industry-born. Sports-driven.

HARDWARE

Carabiner on anchoring point side:
KOBRA TW

MATERIAL

Material:
Aluminium, Steel, Polyamide